Unisto Hi-Genius











© Unisto, www.unisto.com

The ISO 17712 certified and C-TPAT compliance High Security Bolt Seal is the number one solution to seal Freight Containers, Truck Doors, Trailers and Goods Wagons. Very popular in the Shipping, Transport, Air Cargo and Retail industries. A tensile strength of more than 1000 kg prevents opportunistic theft. Removal requires special bolt cutters. Permanent marking of customer name and consecutive numbering or barcode for fast, accurate data capture. Available in a range of plastic colours.

Certificate ISO 17712 Hi-Genius

Certificate ISO 17712 Hi-Genius (bare-pin)


Features of this security seal

Type of Seal
Bolt Seals

Application
Container

- Interlocking petals when closed provides evidence of attempted tampering by spinning
- Steel locking body increases security level
- Steel components excel the requirement of a minimum diameter of 18 mm
- Pulling force 1‘000 kg minimum prevents opportunistic theft
- Customer name /logo for clear identification
- Laser engraved numbering - impossible to change, increases security leve
- Numbers on bolt and body prevents substitution of component parts
- Hi-Genius is fully ISO 17712:2013 compliant, incl. clause 6 “Testing for Evidence of Tampering”
- available in ABS coated steel pin or bare steel pin configurations

© Unisto, www.unisto.com



Materials
Bolt: steel, silver zinc pattern
Body and spring: steel
Coating: Acrylonitrile Butadiene Styrene (ABS)

Tensile strength
Above 10 kN (1000kg)

Numbering
up to max. 7 digits

Barcoding
barcode 128, interleaved 2/5, others on request

Customer name/logo
Directly laser marked

Plastic colours (laser)
pink, light blue, light yellow, ligth green and white


Packing
Tray - 10 pieces per tray, 200 seals per carton Box - 20 pieces per box, 200 seals per carton Polybag - Individual pack, 10 pieces per polybag, 200 seals per carton (Bare metal pin configuration only)


Packing size
inner box 280 x 59 x 87 mm

carton	tray type	405 x 210 x 215	mm	16.0kg
	box type	310 x 298 x 190	mm	17.7kg
bare metal pin type	box type	450 x 210 x 215	mm	11.5 kg


© Unisto, www.unisto.com

How to close





How to open



© Unisto, www.unisto.com